

Bilanx bathing collection strike the balance Design Safety

Bowed Grab Bar with Towel Bar

Stainless steel screws for wood backing & 4 hollow wall togglers included with every bar! * Wingit Compatible (wingits sold separately)

HH – 2500 Series

Bowed Grab Bar with Towel Bar

Application Use:

Architectura

mmercial

nstitution

Residentia

Specifications

With a beautiful, high-falling curve that combines the functionality of a grab bar and towel bar. The Bowed Grab Bar with Towel Bar can support weight up to 250lbs. when properly installed. It is made from high quality 18 gauge 1.25" diameter 304 stainless steel and available in left-handed or right-handed configurations.

Convenient mounting flange post with set screws allow for easy flange access during installation yet preserving the clean finished look of the concealed flange cover. Using a wingit compatible flange base and 5 optional screw hole ports makes locating on a stud or hollow wall even easier than ever. 4 hollow wall togglers included with every bar.

The Bilanx Collection has been designed, built, and tested to 250lbs exceeding HUD, FHA, VA, ADA, ANSI and other federal, provincial, and local codes.

*Grab Bars can only be as strong as what they are mounted to. It is imperative when installing any safety product to consult with a qualified contractor to insure you have the sufficient backing to support the seat.




The Bathing Collection

All Bowed Grab Bars with Towel Bar ship complete with easy to follow instructions, mounting hardware for stud framing and hollow walls. The Bilanx Collection has been designed, built and tested to 250lbs.

The Bowed Grab Bar with Towel Bar comes in 4 standard finishes.

RIGHT HANDED CONFIGURATION:

HH-2500 RH-SS	SATIN FINISH STAINLESS STEEL
HH-2500 RH-PC	POLISHED CHROME
HH-2500 RH-OWB	OLD WORLD BRONZE
HH-2500 RH-MB	MATTE BLACK



LEFT HANDED CONFIGURATION: (shown)

HH-2500 LH-SS	SATIN FINISH STAINLESS STEEL
HH-2500 LH-PC	POLISHED CHROME
HH-2500 LH-OWB	OLD WORLD BRONZE
HH-2500 LH-MB	MATTE BLACK

Custom Finishes Available Upon Request

Dimension tolerances +/- 3/16"