

Wall to Floor w/Outrigger - right & left

*wingit compatible

Configuration: 15-16

Grab Bar

Twist-Lock Concealed


Application Use:

Architectural Commercial Institutional Residential

Specifications

Wall to Floor Safety Bar with outrigger and snap on / twist-lock concealed flanges. Manufactured by ELCOMA from 18 gauge, type 304 stainless steel, satin finished, tubing. 14 gauge stainless steel mounting flanges, heliarc welded to the tube to form a single structural unit.

ELCOMA grab bars are designed, built, and tested to withstand 250lbs. (113kgs) of load when properly installed.* This exceeds HUD, FHA, VA, VA, ADA, ANSI and other federal, provincial, and local codes. *Grab Bars can only be as strong as what they are mounted to. It is imperative when installing any safety product to consult with a qualified contractor to insure you have sufficient backing.






Custom sizes are available to suit special requirements.

The exclusive ELCOMA concealed flange system adapts both "Twist-Lock" and "Snap-On" compatibilities making installation a breeze. ELCOMA Wall to Floor Bars come in 1.25" & 1.5" Diameters with a variety of finishes & coatings.

Bar Diameter:	1.25" , & 1.5"
Bar Grip:	Smooth, Peened, Knurled, Shur-Grip (available in 1.25" only)
Standard Flange:	Twist-Lock / Snap-On concealed * Wingit compatible
Optional Flanges:	Bolt, Exposed, & Female Thread Insert
Standard Finishes:	Satin Finish, White or Almond Powder Coating
Custom Finishes:	Multiple colors & finishes available, call your representative or
	visit www.elcoma.com for selection grid.
Configurations:	Standard: 33"x30"



ORDER ENTRY BY FAX 888.802.8186 OR EMAIL orders@healthathomeinc.com
Office 704.960.0148 or 980.900.2845 www.healthathomeinc.com

Products that enhance safety, vitality, & longevity at home.